

ES V8 Air/Water Heat Pumps

AWST-R32-S 6, 9 & 12 kW Split Series

Economic and effective air-to-water heat pump, designed for a Nordic climate

- 6, 9 and 12 kW heating capacity
- 250-liter domestic hot water storage tank
- A+++ heating efficiency
- User-friendly touch display
- Internet connectivity, monitor your heating through your mobile
- Two different temperature zones
- Automatic restart in case of power failure
- Operates in conditions down to -30°C
- Short payback time
- Low noise outdoor unit
- Split system, no antifreeze protection is required
- Built in backup heater for heating/hot water
- KEYMARK certified



User-friendly touch screen interface

The interface enables quick adjustment of all temperature settings directly from the front page. The software also supports variable temperature settings (curve) for both heating and cooling.



ES V8 Air/Water Heat Pumps

AWST-R32-S 6, 9 & 12 kW Split Series

Converts energy from the outdoor air to heat and domestic hot water.

By utilizing the energy from outdoor air, you can reduce your energy bills in an eco-friendly way, and at the same time creating the perfect level of comfort for your home. AWST-R32-S is designed to replace or supplement an existing heat source or for new installations and will typically reduce your energy consumption from 60–80%. The indoor unit has a stylish design to fit into a modern home. All connections are easily accessible at the top of the unit. Designed to provide maximum energy savings and quiet operation. All AW-R32-S series are rated A+++ when used in low temperature applications and A++ in high temperature applications.

Control system

The unit is a complete heating/cooling/hot water central within 60x65 cm floor area.

The built-in 250 liter tank provides enough hot water for most households. Large tap profile and high efficiency reduces the cost of a shower by 60–70%. It has safety valve kit, 11 liter expansion, power full class A water pump that can run most villa heating systems, thermostatic hot water mixing valve. Weather compensated water temperature setting combined with internal room sensor provides you with all needed temperature control suitable for most buildings.

Increase your savings

The control system automatically changes between operation mode based on your settings. You can optimize the running based on your household logistics, like store more hot water when electricity prices are low, lower the temperature when no one are home in different periods every day, 7 days a week. It is also preserved for utility operation from your network provider, that can control the

heat pump and balance the available power in the network.

Split system enables the advantage that no water is lead outside the house, and special antifreeze protection that drains efficiency is not required. Slim refrigerant pipes are easier to route and cover. The automatic and self-learning defrost function, combined with the nanocoated evaporator, reduces defrosting time to a minimum and increases the efficiency. Different heating systems require different temperatures, e.g. floor heating and radiators. AWST-R32-S have the possibility to set two heating curves if you have two different heating systems in your home. If the temperature drops, the heat pump automatically increases the water temperature to compensate for higher heat loss in the building. If additional power is required, the integrated electric heaters will be used as back-up.

	Unit	AWST6 – R32-S-V8	AWST9 – R32-S-V8	AWST12 – R32-S-V8
Article number (indoor/outdoor unit) ¹		120335/120324	120335/120325	120335/120326
ErP Energy efficiency class		A+++ / A++	A+++ / A++	A+++ / A++
SCOP 35°C (floor heating) EN 14825		4.74	4.73	4.71
Tap water profile		L/A+		
HEATING MODE (A7/W35)				
Heating capacity*	kW	3.50 – 6.50	4.30 – 9.20	5.50 – 11.60
COP max - Coefficient of Performance*	W/W	4.70	4.71	4.90
Rated input power*	kW	0.75 – 1.41	0.92 – 2.10	1.10 – 2.68
Max. temperature of heating water	°C	58		
Operating range heating	°C	-30 to +45		
DHW TANK				
Type		SUS316 Steel, DHW storage type		
Volume	l	250		
COOLING MODE				
Cooling capacity**	kW	6.22 – 7.45	6.70 – 9.50	7.00 – 9.80
EER max – Energy Efficiency Ratio**		4.45	4.60	3.80
Min. temperature of cooling water	°C	7		
Operating range cooling	°C	+8 to +65		
POWER SUPPLY – SPECIFICATIONS				
Outdoor unit	V/ph/fuse	230V / 1-ph / 10A/C	230V / 1-ph / 16A/C	
Indoor unit + electric flow heater	V/ph/fuse	230V / 3-ph / 25A/C or 400V / 3-ph / 16A/C		
REFRIGERANT SPECIFICATION				
Type / Mass of refrigerant	kg	R32 / 0.90	R32 / 1.40	R32 / 1.80
Type of connection between indoor-outdoor unit		Refrigerant flare connection		
Dimensions of refrigerant pipes connectors	Inch	¼ and ½	3/8 and 5/8	
SOUND POWER AND SOUND PRESSURE LEVEL				
Sound power level LwA - Indoor unit	dB(A)	44	45	45
Sound power level LwA - Outdoor unit***	dB(A)	52	53	52
NET DIMENSIONS				
Indoor unit (WxDxH)	mm	600 × 707 × 1 720		
Outdoor unit (WxDxH)	mm	1 025 × 397 × 750	1 207 × 412 × 900	1 207 × 412 × 900
NET WEIGHT				
Indoor unit / Outdoor unit	kg	118 / 83.5	118 / 90	118 / 93.5

¹ It is mandatory for articles 120316, 120329 and 120335 to be installed with an electric anode (art. 120800) to ensure corrosion protection in markets where the water requirements are difficult to achieve.

* Measured according to standard EN 14511. Heating condition: water inlet/outlet temperature 30°C/35°C, ambient temperature DB/WB 7°C/6°C. ** Measured according to standard EN 14511. Cooling condition: water inlet/outlet temperature 18°C and ambient temperature 35°C. *** Measured according to standard EN 12102. /WB 34°C.

ES ENERGY SAVE HOLDING AB (PUBL)

Metallgatan 2–4, SE-441 32 Alingsås · Sweden

0046 322-790 50 · info@energysave.se · www.energysave.se

 **ENERGY SAVE**